

NOTES:

- 1. THE METER ASSEMBLY TO BE INSTALLED ON PRIVATE PROPERTY. EASEMENT REQUIRED.
- A MINIMUM 4 FT. CLEARANCE ON EACH SIDE OF THE METER ASSEMBLY MUST BE MAINTAINED FOR METER TESTING AND MAINTENANCE.
- ы O.U.C. INSTALLED: O.U.C. TO PROVIDE AND INSTALL METER W/STRAINER AND BY-PASS ASSEMBLY (AT DEVELOPERS EXPENSE) ALL OTHER MATERIALS TO BE PROVIDED AND INSTALLED BY THE DEVELOPER /CUSTOMER PER O.U.C. SPECIFICATIONS.
- 4. W/STRAINER (AT DEVELOPERS EXPENSE). ALL OTHER MATERIALS TO BE PROVIDED AND INSTALLED BY THE DEVELOPER/CUSTOMER PER O.U.C. SPECIFICATIONS DEVELOPER INSTALLED: O.U.C. TO PROVIDE METER UNDER O.U.C. INSPECTION
- ù THE BACKFLOW PREVENTION DEVICE (O.U.C. APPROVED) TO BE FURNISHED, INSTALLED, OWNED & MAINTAINED BY THE DEVELOPER/CUSTOMER.

- 6. FOR CONSTRUCTION AND BACKFLOW PREVENTION REQUIREMENTS CONTACT O.U.C. INSPECTION DEPARTMENT AT 407-434-2535.
- 7. FOR SENSUS T2 SERIES DOMESTIC METER FLOW DATA & SPECIFICATIONS VISIT WWW.SENSUS.COM.

CONSTRUCTION NOTES:

._

- SERVICE VALVE, PIPE & FITTINGS TO BE ONE NOMINAL SIZE LARGER THAN METER SIZE.
- BYPASS ASSEMBLY VALVE, PIPE & FITTINGS SAME SIZE AS METER.

5

4. ы THE OUC OWNED PORTION OF METER ASSEMBLY SHALL NOT BE IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY O.U.C. OR THE METER MANUFACTURER PRIOR TO CONSTRUCTION. THE CURRENT METER & SPOOL PIECE DIMENSIONS THROUGHT

PAINTED UNLESS APPROVED BY OUC.

MATERIAL LIST

- ≻ (SIZE") D.I. PIPE (VARIOUS LENGTHS)
- $\boldsymbol{\varpi}$ (SIZE") M.J. GATE VALVE W/BOX (SERVICE VALVE)
- (SIZE") X (SIZE") M.J. TEE
- (3) MEGALUG JOINT RESTRAINTS
- (SIZE") x 30" D.I. PIPE STUB
- (SIZE") M.J. ELL
- (2) MEGALUG JOINT RESTRAINT
- (SIZE") M.J. GATE VALVE W/BOX (VALVE NUT LOCKING CAP PROVIDED BY O.U.C.) (2) MEGALUG JOINT RESTRAINT (SIZE") FLANGED D.I. PIPE
- (SIZE") FLANGED ELL (LONG RADIUS)
- (SIZE") FLANGED GATE VALVE (NRS) W/HANDWHEEL
- FLANGED X FLANGED D.I. SPOOL PIPE SEE TABLE FOR SPOOL PIECE LENGTH (SIZE") TURBO METER W/STRAINER
- \vdash (PROVIDED BY O.U.C. AT DEVELOPER'S EXPENSE) (SIZE") x 2" SERVICE CLAMP 2" BRASS CLOSE NIPPLE 2" GATE SCREW VALVE 2" BRASS PLUG SEE TABLE FOR METER LAY LENGTH

(SIZE") FLANGED TEE

- REDUCED PRESSURE BACKFLOW PREVENTER ASSEMBLY (O.U.C. APPROVED)
- 3000 PSI CONC. W/6X6 WWF (6' WIDE x 8" THICK MINIMUM) BY DEVELOPER
- ADJUSTABLE BRACE (AS NEEDED)
- EXPANSION JOINT MATERIAL (TYP.)
- REFER TO CONSTRUCTION NOTE 3.

	12" X 10"	10" X 8"	8" X 6"	6" X 4"	4" X 3"	SERV. X METER DIA. (IN)
)	41-1/8"	30-1/8"	27"	23"	19"	* (K) METER LAY LENGTH (IN)
	12" FLG. X 10" FLG. X 50"	10" FLG, X 8" FLG, X 40"	8" FLG, X 6" FLG X 30"	6" FLG. X 4" FLG. X 20"	4" FLG. X 3" FLG. X 15"	SERV. X METER * (K) METER LAY * (J) METER SPOOL DIA. (IN) LENGTH (IN) PIECE (IN)
	10"	8"	6'	4"	4"	BYPASS DIA. (IN)

SCALE N/A	ACAD No. N/A	W.R. No. N/A	DATE 06-25-2012 S.G.	DRAWN WETS	ENG. W.E.	The <i>Reliable</i> One		
FILE DOM MASTER MTR (TYP).DWG MAP SEC. N/A	STANDARD SIZES: 3" 4" 6" 8" 10"	W/U.U.C. AFFROYBU KEDUCEU FRESSURE DACAFLUM FREYENIER	M /O II O ADDICATE AND THE CONTROL OF THE CONTROL O	DOMESTIC MASTER METER ASSEMBLY (TVDICAL)		3800 Gardenia Ave. Orlando, FL. 32839	ORLANDO UTILITIES COMMISSION WATER BUSINESS UNIT	